

Performing Arts
Division – Technical
Support Unit

Hong Kong Cultural Centre

10 Salisbury Road Tsim Sha Tsui, KLN, HK, China

Phone 852-2734 2009

Fax

852-2739 0066

CONTACTS

Carrie Lo

Senior Manager (HKCC/Venue) Direct Line 852- 2734 2821

Katharine Ng

Manager (House Management) Direct Line 852- 2734 2804

Annie Chan/ Michael WU

Acting Resident
Technical
Manager(HKCC)
rdtmhkcc1@lcsd.gov.hk
rdtmhkcc2@lcsd.gov.hk
Direct Line
852- 2734 2814
Fax Line
852- 2739 0066

GENERAL SET-UP

The Studio Theatre operates on a 'bare-walls' touring policy. That is, all equipment is normally set-up and struck within the booking period. Hirers are reminded to allow sufficient preparation time to hang theatre masking, rig all stage lighting and set up audio system.

Hong Kong Cultural Centre – Studio Theatre Basic Technical Information

	V. 2024.03.12	03.12 Page 1		
			III A THE	
	Seats	End stage	321	
		Thrust Stage	303	
		Arena stage	496	
		Transverse Stage	382	
	Stage Size	End Stage	13.40 x 9.88m (W x D)	
		Thrust Stage: Down Stage	8.24 x 9.55m	
		Up Stage	13.35 x 5.35m	
		Arena Stage	8.24 x 8.24 m	
	Ctogo Hoight	Transverse Stage Stage – underside of lx bridges	13.40 x 8.13m	
	Stage Height	Stage – underside of ix bridges Stage – underside of grid	8.20m 9.20m	
		Stage – underside of grid Stage – underside SL gallery	3.20m	
		Stage – underside SR gallery	3.40m	
	Stage Surface	Flat – hardboard.		
	Trap	Grave trap - 3.00 x 1.00m (For End	Stage, grave trap	
		cannot be used).		
	Machinery	6 Chain hoists, capacity 250kg (nee	(needs set up time). (pick	
		up, set up, dismantle and return to s		
	Flying system	8 Spotted hemp sets at main stage.		
	Stage Manager	Working corner US – Intercom syste		
ζ .	Desk	Dressing room paging and Show rel		
	Wardrobe	None – iron & board available. 1 wa	sning machine & 1 dryer	
	Dressing	at level 4 dressing rooms. 2 for 24 persons, with toilet and sho	wor	
	Rooms	2 for 24 persons, with tollet and sho	WGI.	
	Electrics	ETC Gio control console in control r	oom at technical gallery.	
		ETC Sensor 3 Digital Dimmer 2.5kV	•	
		ETC Sensor 3 Digital ThruPower Di		
		6 x light bridges over stage, cycloral	ma lights, ground row,	
		Lx tower x 6.		
		Additional power: 200A x 3 phase x		
	Sound	28 ways DIGICO SD10 mixing cons	-	
	Projection (extra charge	Panasonic PT-D6000ES with 6000 Panasonic PT-RQ25K	ANSI iumens	
	(extra charge incurred)	Panasonic PT-RQ25K		
	Storage Space	Limited off stage area.		
	Get-in	Cargo lift from ground floor, size 2.8	30 x 1.83 x 1.90m (W x	
		D x H).	,	
	Crossover	Passage behind stage and/or seating	ng.	
	Equipment	Black Masking - borders, legs, wrap	•	
		screen, braces, weights, musiciar	n chairs, music stand,	
	la a fan e e e	cougar lifts, ladders, etc.		
	Instruments	Yamaha YUS 5 upright piano.		
ţ				

V. 2024.03.12 Page 2 of 2

INFORMATION Full technical drawings available	Comments	Operates on a bare walls policy, all equipment needs to be set-up and struck within booking period.
diawings available		