

Ko Shan Theatre New Wing - Auditorium

FULL Technical Information

Performing Arts
Division –
Technical Support
Unit

Ko Shan Theatre

77 Ko Shan Road Hung Hom Kowloon, HK

Phone

852-2740 9222

Fax

852-2781 4783

CONTACTS

Alice CHAN

Senior Manager (KW) Direct Line 852- 2740 9219

Dinah CHOO

Manager (KST)H&M Direct Line 852- 2334 6378

Karen LAU

Resident Technical Manager(K) Direct Line 852- 2330 4761 852- 2329 7135

Fax Line 852- 2365 0503

GENERAL SET-UP

Auditorium of Ko Shan Theatre New Wing operates on a basic setup policy. That is, all equipment has a prerigged position at the start of bookings. Hirers requiring to move or remove equipment must do so (and reinstate it) within their booking period.

Check with our Technical Manager for any other equipment and technical enquiry.

V. 2024.04.10 Page 1 of 8





Auditorium of Ko Shan Theatre New Wing is a traditional proscenium theatre and fully equipped to support Chinese opera, dance, drama, music concert, talk and variety performances.

DIRECTIONS

MTR:

Kwun Tong Line, Ho Man Tin Station, Exit A2

Tuen Ma Line, To Kwa Wan Station, Exit C

Tsuen Wan Line, Mong Kok Station, Exit B2 → Mini bus routes no. 27M

Freeway (From S to N):

Cross Harbour Tunnel → Hong Chong Road → Chatham Road North → Pak Kung Street (turn right) → Ko Shan Road

Freeway (From N to S):

Boundary Street → Waterloo Road → Princess Margaret Road → Fat Kwong Street → Shun Yung Street → Ko Shan Road



LOADING

Clearance of truck: 4.70m

Dock Height: 0.87m Steel door opening: 3.8m x 3.0m (W x H)

Cargo lift:

1.7 x 2.5 x 2.0m (W x H x D)

Lift Door:

1.68 x 2.38m (W x H)

PARKING

Permit required



Size of truck:

20ft container truck and vehicle longer than 11m require to bring-in loading ramp

16 ton truck with tail lift is recommended (~ length: 8.5m)

V. 2024.04.10 Page 2 of 8

AUDITORIUM



Total Seating: 596

Stalls: 495

Balcony: 101

PROSCENIUM

Structural opening

Adjustable proscenium opening with header and tormentor

13.00 x 7.50m (W x H)

13.00 x 7.50m (W x H)

9.00 x 5.00m (W x H) Min. 13.00 x 7.50m (W x H) Max.

STAGE WIDTH


Centreline to stage right 12.00m
Centreline to stage left 13.70m

STAGE DEPTH

Rear of Proscenium to cyclorama on centreline	11.28m
Rear of Proscenium to forestage on centreline	1.60m
Rear of Proscenium to orchestra pit edge on	4.70m
centreline	
Forestage radius	11.65m
Forestage arc length	13.70m

STAGE HEIGHT

Clearance under grid	20.00m
Maximum bar flying height	
Counterweight bar	19.20m
Motorised - house curtain, curtain bar 24 and 36	16.96m
Motorised - lighting bar 2, 5, 15, 29 and 41	17.69m
Motorised - lighting bar 50	7.20m
Motorised - side lighting bar SL1 and SR1	14.78m
Motorised - side bar SL2 and SR2	17.69m
Motorised - FM bar 1, 2, 3	9.59m
Above auditorium	1.00m



FORESTAGE / ORCHESTRA PIT

Curved forestage/pit lift area, suitable for 15 persons

Orchestra pit area 30.00m² approx.

Depth 3.00m Centre
1.10m Ends
Static load 500kg/m² SWL
Dynamic load 250kg/m² SWL

Pit setup provision with chairs, stools, music stands, and music lights

STAGE FLOOR

Flat black hardboard 750kg/m² SWL

Trapdoor - None

Equipped with footlight trough and dip sockets

V. 2024.04.10 Page 3 of 8

SIDE STAGE

 Stage right
 2.50 x 12.65m (W x D)

 Stage left
 4.20 x 12.65m (W x D)

REAR STAGE

None

STORAGE SPACE

Stage right $12.10 \times 6.00 \text{m} \text{ (W x D)}$

CROSSOVER

Corridor behind stage

RIGGING

House Curtain (Red) - motorised

Fly-in and out 10 Sec (Max.) Open and close 15 Sec (Max.)

Rigging system

Bar diameter 48.30mm

Stage bar - counterweight 41

Bar 1 to 50 (except 2, 5, 15, 24, 29, 36, 41, 47 and 50)

Length 15.00m (1m extend on both sides)
Capacity 600kg SWL

Lighting bar - motorised 5

Bar 2, 5, 15, 29 and 41 length 15.00m (1m extend on both sides)

Capacity 650kg SWL

Bar 50 length 15.00m

Capacity 450kg SWL

Curtain bar - motorised 2
Bar 24 and 36 length 16.00m

Capacity 400kg SWL

Side bar - motorised 4
SL 1, SL 2, SR 1 and SR 2 length 9.50m

SL 1, SL 2, SR 1 and SR 2 length 9.50m
Capacity 9.50m
650kg SWL

Forestage bar - motorised 3

FM 1, FM 2 and FM 3 length 15.00m

Capacity 650kg SWL

Rolling beam above grid (A) 4
Compartment 2

Beam per compartment 2
Hoist 4

Hoist capacity 650kg SWL

Low dead : 1.0m above stage

Offstage runway beam above grid (B) 2


5.20m from centre line to SL /SR

Hoist SL / SR 2 / 2

Hoist capacity
Low dead : 1.0m above stage
*Need field verification by the hirer

*Need field verification by the hirer

650kg SWL



V. 2024.04.10 Page 4 of 8

Grid floor capacity				250kg/m² SWL		
Loading gallery at grid capacity (SL)		250kg/m² SW				
Fly gallery capacity of Stage left Stage right Crossover	2/F, 3/F and 4/F			450kg/m² SWL 450kg/m² SWL 250kg/m² SWL		
STAGE EQUIPMENT Stage drapery Black masking leg bord half side	12 der 6 1	flat flat flat flat flat flat		4.00 x 8.60m (W x H) 16.70 x 4.00m 14.80 x 1.50m 9.60 x 8.60m 3.00 x 8.45m 3.00 x 9.67m		
Cyclorama	1	flat		17.00 x 9.00m		
Orchestra Riser Wenger Trouper Aluminum frame platf Chair rails and guard No drilling or painting 2.40 x1.20m (W x L)		H) x 4				
Choir riser (3 or 4 ste	eps) 7		Wenge	er Tourmaster		
Musician chair	40		Black			
Music stand	50		Black			
Conductor platform	1					
Conductor music sta	and 1					
Podium	1					
Ceremony chair	18		Red			
Dancing Tile for dance show only (Please allow time to	Black lay the tiles during book	ing time)	7	7 15.00 x 2.00m (Main stage)		
Stage carpet for Chinese opera onl	y Green		2	13.00 x 4.00m		
Instrument Upright piano 18" Chinese drum Timpani			1	Yamaha 1U ADAMS (23", 26", 29", 32") (Incur extra charge)		
			1			
Lifting Platform	Lifting Platform Genie AWP 25S Genie AWP 36S		1 1	operated by competent person only		
Stage weight	12.5kg		45			

V. 2024.04.10 Page 5 of 8

DRESSING ROOM

Basement Band Room: 6 persons

Ground level Room 1-4: 1 person (per room)

> Room 5-7: 2 persons (per room)

First Level Room 8: 6 persons

> 4 persons Room 9: Room 10: 6 persons **Room 11:** 10 persons Room 12: 8 persons

Dressing rooms at ground level fitted with toilet and shower; and dressing rooms at first level fitted with public toilet and shower.



1 washing machine and 1 dryer located at 1st floor.

Iron, iron board (1 set) and steamer (1 pc) are available upon request.

LIGHTING

236 channels of ETC HD15 3kW and 24 channels of ETC HK15AF 3kW Dimmer

Dimmer room at 2nd floor stage right

Control Board ETC Gio of 2048 outputs, with full back up control facilities, located in lighting control

room at rear of Balcony

Houselights Dimmer controlled. Controlled independently or via lighting control board.

260 x 3kW production lighting circuits, fixed wiring type, circuits are terminated to 15A Circuit

socket outlets to UK standard respectively on the production lighting boxes, distributed at

various locations throughout the Stage and lighting bridges

DMX gateway 1 port ETC N31G-F (5-pin XLR female) distributed at various locations **DMX Socket**

throughout the stage and lighting bridges

Additional Power USR: TP&N MCCB board '200AUX' power feeding for 100A x 1, 63A x 3, 32A x 2

industrial 5 pin socket outlet

Loading bay: 63A TPN isolator along with 63A x 1 industrial 5 pin socket outlet

Connection must be conducted by a local registered electrical worker.

Hirer shall supply adequate circuit protective devices for all bring in electrical

installation.

13A wall-mounted socket outlets at UK standard are provided on the stage.

Source 4 Zoom 25-50

ColorSource Spot 25-50

52

14

Front of House

FOH Lighting bar FM 2, at forestage **Position**

750W

185W

ETC

ETC

FOH Lighting bridge no.1, 16.1m throw to CS at 43 degree FOH Lighting bridge no.2, 20.3m throw to CS at 33 degree

FOH Lighting bridge no.3, 23.7m throw to CS at 28 degree

Profile 2kW Robert Juliat 710SX2 10-25 10 750W Source 4 Zoom 15-30 130 ETC

LED Profile 185W ETC ColorSource Spot 15-30 10

Fresnel 1.2kW 20 Selecon Rama 150 F 7-50 **LED Fresnel** 185W ETC ColorSource Spot Fresnel 28

PC 1.2kW Selecon Rama 150 PC 5-60 30

Parcan 1kW Kupo Par-64LB (CP 60) 24 V. 2024.04.10 Page 6 of 8

	1kW 1kW	Kupo Kupo	Par-64LB Par-64LB	,	20 16	
LED Cyc. Light	334W	Chauvet	Ovation C	syc 3 FC	6	
LED Ground Row	334W	Chauvet	Ovation C	Syc 3 FC	6	
LED Automated Lighting	1kW	Robe	DL7S		6	Fixed install at circle front
LED Borderlight	48Vdc	Chroma Q	Color Bloo	ck 2 plus	10	
LED Follow Spot	440W	USHIO	SAI 500		2	
Smoke Generator		Look Solutions	Viper NT		2	
LED Strobe Light	360W	Philips	Showline	Nitro 510	3	
LED UV light	360W	Altman	Spectra U	IV30	4	
Gobo holder Spotlight Applicable ETC Source 4 Profile		Gobo Holder <u>Qty</u> 20 / 35	Gobo I <u>Ty</u> A /	<u>pe</u>	Gobo <u>Size</u> 100 / 86mm	Image <u>Size</u> 68-75 / 65mm
Other	Side ligh	nt tower	600 x 1850 x 860mm (WxHxD) 8			
	Tower e	quipment setup:	3 1kW ETC Sour		Source 4 15/50 Source 4 15/30 Source 4 15/50 Source 4 15/30	1608mm* 1168mm* 728mm* 288mm*
	* = Height of the equipment from to floor					
	LED Mu	sic light			50	

Equipment availability does vary slightly according to equipment conditions and maintenance. Check with Technical Manager for any update.

<u>Hirer will be provided with basic lighting only, from available hung equipment, if technical preparation time is less than 2 hours in the booking.</u>

All brought-in "Electrical and Stage Lighting Equipment" to be used in LCSD PA venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations". Please contact the venue management for any electrical safety concern. Website reference:

https://www.emsd.gov.hk/en/electricity_safety/index.html

Sound

Sound system	Main System	
Central cluster:	L-Acoustics A15i WIDE	3
Left & Right cluster:	L-Acoustics KIVA II	8 (on each side)
Subwoofer:	L-Acoustics SB15m	4 (on each side)
	Fill and Effect System	
Stage front:	L-Acoustics 5XT	6
Orchestra pit front:	L-Acoustics 5XT	4
Balcony delay fill:	L-Acoustics 5XT	4
Side fill and effect:	L-Acoustics X8	4
Ceiling fill and effect:	L-Acoustics X12	5
Surround:	L-Acoustics X8	12

V. 2024.04.10 Page 7 of 8

Main control Console	DiGiCo Quantum 338, digital mixi output x 14, Matrix output x 12) in		
Microphone Tie line	Downstage left Downstage right Upstage left Upstage right Orchestra pit wall box Orchestra pit desk Centre auditorium Rear auditorium Loading bay	6 Mic + 1 Multi (12 chann 6 Mic + 1 Multi (12 chann 4 Mic 4 Mic 4 Mic + 2 Multi (12 chann 4 Mic 1 Mic 4 Multi (12 channels) 4 Mic	nels)
Accessory Electronics (Pre-aligned, not loos	Lexicon MX400XL effect processo	r	1
(Fre-aligned, not loos	se equipment)		
Microphone	AKG 414 AKG CK91 + SE300B AKG CK92 + SE300B AKG C747V11 Crown PCC-160 Shure Beta 57A Shure Beta 58A DPA 2011C DPA 4011 DPA 4099 Countryman I2HS10XLR		3 2 2 4 12 12 2 2 2 2
Wireless Microphone	Shure ADX1Lemo3-G54 (clip) Shure ADX2/K9B-G54 (hand-held Max. 8 units with a minimum bo		8 8 (Incur extra charge)
Stage Monitor	L-Acoustics X12		12
CD	Tascam SS-CDR250N compact d	isc players	2
Mini-Disc	Nil		
Digital Media Player	Oppo BDP-103		2
DVD Recorder	LG RH589H 2		2
Multimedia Projector	Panasonic PT-RQ35K (3-Chip DLI (with Standard Zoom Lens ET-D75LI Long Throw Zoom Lens ET-D75LI	5LE20 and	1 (Incur extra charge)
Computerised LED Surtitle System	Horizontal LED Display Boards (incur extra charges) Default font color: White Two (2) Horizontal display boa proscenium.	rds fixedly installed on	2 the left and right sides of
	Display English, Chinese or English and Chinese texts simultaneously. Size of LED board: 200cm x 100 cm (WxH) The system will display in four lines per page. Each line for maximum 13 Chinese words or approximate 19 English alphabets, include punctuation mark.		

V. 2024.04.10 Page 8 of 8

Surtitle input and stored in Microsoft® Word (*.docx) or text (*txt) file format.

The control computer was set inside sound control room at the back of auditorium. Display on **ALL boards will be identical**.

LED board is set up within booking period when two sessions or more are booked. Setup time normally requires one hour.

COMMUNICATION

Stage manager control panel at stage right with dual channel intercom system

Intercom System Dual channel intercom system with dual channels body-pack

Single channel wireless intercom system

Paging and Show

Replay System

Front-of-house paging/public address, backstage paging located at prompt desk

Show Relay TV High resolution fixed camera for stage house

Standard resolution fixed conductor camera

Standard resolution fixed laser camera for stage house

9" HD TV displays at stage manager's desk 32" LED TV displays at stage left and right

23" LCD monitor for dressing rooms, production office and band room

55" TV displays at G/F stall entrance, 1/F stall foyer, 2/F balcony foyer and VIP lounge

Production Desk Set at the centre of the stall upon request.

EMERGENCY FOH ANNOUNCEMENT SYSTEM

UPS maintained FOH emergency announcement system with hand-held wired microphone.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal.