

Performing Arts
Division –
Technical Support
Section

Ko Shan Theatre

77 Ko Shan Road Hung Hom Kowloon, HK Phone 852- 2740 9222 Fax 852- 2781 4783

CONTACTS

Alice CHAN

Senior Manager (KW) Direct Line 852- 2740 9219

Dinah CHOO

Manager (KST)H&M Direct Line 852-2334 6378

Karen LAU

Resident Technical Manager(K) Direct Line 852- 2330 4761 852- 2329 7135 Fax Line 852- 2365 0503

GENERAL SET-UP

The Ko Shan Theatre operates on a basic setup policy. That is, all equipment has a prerigged position at the start of bookings. Hirers requiring to move or remove equipment must do so (and reinstate it) within their booking period.

Check with our Technical Manager for any other equipment and technical enquiry.

Ko Shan Theatre – Theatre FULL Technical Information

V. 2024.04.11 Page 1 of 8





Ko Shan Theatre is a traditional proscenium theatre, but without a full fly tower, which limits its technical abilities. Primary use is for Chinese Opera and Chinese Dance. Secondary use is for Drama, Concerts and Assemblies.

DIRECTIONS

MTR:

Kwun Tong Line, Ho Man Tin Station, Exit A2

Tuen Ma Line, To Kwa Wan Station, Exit C


Tsuen Wan Line, Mong Kok Station, Exit B2 → Mini bus Routes No. 27M

Freeway (From S to N):

Hung Hom Cross Harbour Tunnel →
Hong Chong Road → Chatham Road
North → Pak Kung Street (turn right)
→ Ko Shan Road

Freeway (From N to S):

Boundary Street \rightarrow Waterloo Road \rightarrow Princess Margaret Road \rightarrow Fat Kwong Street \rightarrow Shun Yung Street \rightarrow Ko Shan Road



LOADING

Clearance of truck: 4.70m Steel Door Opening: 2.73 x 4.56m (W x H)



PARKING

Permit required

V. 2024.04.11 Page 2 of 8

AUDITORIUM



Total Seating: 1031

Stalls: 916 Balcony: 115

Major seats are disposed in a wide Stalls fan with seats in a shallow Balcony.

PROSCENIUM

Structural Opening
Adjustable proscenium opening with Teaser and Tormentor


12.97 x 4.96m (W x H) 12.00 x 5.00m (W x H) Max.

STAGE WIDTH

Centreline to stage right 8.48m
Centreline to stage left 8.48m

STAGE DEPTH

Rear of Proscenium to cyclorama on centreline	11.59m
Rear of Proscenium to cyclorama at sides	7.52m
Rear of Proscenium to cyclorama surround bar on	11.30m
centreline	
Rear of Proscenium to last full cross-stage bar	7.35m
Rear of Proscenium to forestage on centreline	3.42m
Forestage radius	13.00m
Rear of Proscenium to orchestra pit edge on	2.90m
centreline	
Orchestra pit radius	10.17m



STAGE HEIGHT

Clear under grid7.00mMaximum bar flying height6.30mAbove Auditorium1.00m

FORESTAGE / ORCHESTRA PIT

Formed by removing trap and lowering centre lift, maximum for 12 persons

Centre pit lift 8.40m²
Lift and infill area 14.06m²
Depth 2.22m

Pit setup provision with chairs, stools, music stands, and music lights

STAGE FLOOR

Flat black hardboard
Trapdoors - None

Footlight trough and Dip sockets

V. 2024.04.11 Page 3 of 8

SIDE STAGE

 Stage Right
 4.69 x 4.92m (W x D)

 Stage Left
 6.09 x 4.82m (W x D)

REAR STAGE

Not Available

STORAGE SPACE

Limited space

CROSSOVER

Corridor behind stage

RIGGING

House Curtain (Violet) - festoon type

Rigging System

 Motor Bars
 7

 Bar 7, 12, 18, & 23
 16.00m

 Bar 28
 14.00m

 Bar Diameter
 48.50mm

 Capacity
 250kg SWL

Bar B, C 11.00m Capacity 500kg SWL

Electrics Bars 5
Bar 3, 10, & 21 15.50m
Bar 29, & 30 10.00m
Capacity 500kg SWL

 Wiper Track
 9

 Bar 8, 9, 13, 14, 19, 20, 24, & 26
 27.50m

 Bar A
 13.00m

 Capacity
 250kg SWL

Fix overlap curtain set 3
Bar 11, 16, & 27 16.00m

Cyclorama Curved track 1
Bar 34 17.65m
Capacity 250kg SWL

 Hemp set (For Cloth Drop only)
 8

 Bar Diameter
 51.00mm

 Bar 6, 15, 17, 22, & 25
 16.10m

 Bar 31
 11.50m

 Bar 32, & 33
 10.10m

Pinrail None

Side Bars None

Point Hoists None

STAGE EQUIPMENT

Stage Drapery

V. 2024.04.11 Page 4 of 8

Black masking	leg	6	flat	3.00 x 6.25m	(W x H)
	· ·	2	flat	2.00 x 6.30m	,
	border	1	flat	18.00 x 1.80m	
		3	flat	18.00 x 1.50m	
		1	flat	16.00 x 1.55m	
		1	flat	16.00 x 1.20m	
	half tab	6	flat	9.00 x 6.90m	As 1 st , 2 nd , & 3 rd mid-curtain
Wrap round Blac	ck cyclorama	2	flat	9 60 x 6 25m	

flat vvrap round Black cyclorama 9.60 x 6.25m

Orchestra Riser Wenger Portmaster.

Aluminum frame platform.

Chair rails and guard rails available. No drilling or painting. 2.40 x1.20m (W x L) 203mm(H) x 4

407mm(H) x 4 610mm(H) x 4

Choir Riser (3 steps) 6 Wenger Tourmaster

60 **Musician Chair** Black

Music Stand 20 Black

Conductor Platform

Conductor Music Stand

Stool

Podium 1

Red 12 **Ceremony Chair**

Dancing Tile Black for main stage

for dance show only (Please allow time to lay the tiles during your booking time)

Stage Carpet

2 13.00 x 3.50m for Chinese opera only Pale Green

Upright Piano Upright piano Yamaha U1 Instruments

18" Chinese Drum

Lifting Platform Upright UL-24 1 operated by competent person

20 12.5kg **Stage Weight**

DRESSING ROOM

Level 1 Room 1: 4 persons Room 1a: 2 persons

Level 2 Room 2, 3: 4 persons (each room)

> No. 4: 12 persons

Level 3 No. 5, 6: 12 persons (each room)

All dressing rooms at level 2 & 3 fitted with private and public toilet and shower

Quick change facilities downstage right and left.



V. 2024.04.11 Page 5 of 8

RUNNING WARDROBE

None.

Iron & board and steamer are available upon request.

LIGHTING

192 channels of ETC Sensor3 3kW dimmers locating in Lighting Control Room **Dimmer**

Control Board grandMA3 Light 4096 outputs, with full back up control facilities, located in Lighting Control Room

Houselights Dimmer controlled. Controlled independently or via lighting control board.

192 x 3kW production lighting circuits, fixed wiring type, circuits are terminated to 15A socket **Circuits**

outlets to UK standard respectively on the production lighting boxes, distributed at various

locations throughout the Stage and lighting bridges.

Additional

DSR: 220/380 Volt; 3-phase/4 wire, 160A/phase, c/w 160A clamping bus bar;

Power DSR: 220/380 Volt; 3-phase/4 wire, 63A/phase, c/w two 32A sockets for temporary cable

connection.

Conducted by the local registered electrical workers.

The hirer shall supply adequate circuit protective devices for your own electrical

installation.

13A wall-mounted socket outlets to UK standard are provided on the stage.

Front of House FOH Lighting Bar, 5.75m throw at 47 degree

FOH Lighting Bridge no.1, 11.00m throw at 38 degree **Position**

FOH Lighting Bridge no.1, 9.19m throw at 48 degree (Apron)

	r on Eighang Energe herr, on om an en et io degree (i ipren)				
Profile	750W 750W 750W	ETC ETC ETC	Source 4 15/30 Source 4 19 Source 4 10	50 7 20	
LED Profile	167W	ETC	Source 4 Lustr2 15/30	28	
Fresnel	2kW 1kW 1kW	Strand Strand Strand	Patt 828 Cantata F Harmony F	2 18 40	
Parcan	1kW 750W	ETC	PAR 64 CP61 Source 4 PARnel	24 6	
LED Par	135W	Altman	AP-150	50	
LED Cyc. Light	200W	Altman	Spectra Cyc200	8	Electric Bar 30 (No. 5 Lx Bar)
LED Ground Row	200W	Altman	Spectra Cyc200	8	Bottom
LED Automated Lighting	1kW	Robe	DL7S	2	
LED Batten	210W	ETC	ColorSource Linear2	8	
LED Follow Spot	600W	Robert Juliat	OZ-1169	2	Auditorium Perch
Smoke Generate	or	Look	Viper NT	2	

V. 2024.04.11 Page 6 of 8

		Solutions				
Strobe Light	1.5kW	Anytronics	DeathSta	ar	2	
UV light	40W 175W	Griven Wildfire	GR0101 VioStorm	1	4 2	
Gobo holder Spotlight Appli ETC Source 4 F		Gobo Ho <u>Qty</u> 20 / 20		Gobo Holder <u>Type</u> A / B	Gobo <u>Size</u> 100 / 86m	Image <u>Size</u> m 68-75 / 65mm
Other	Side light tower		712 x 5	58 x 2097 mm	8	
	Tower equipme	nt setup:	5(top) 4 3	1kW Stran	nd Harmony F nd Harmony F nd Harmony F	1880mm* 1473mm* 1067mm*

* = Height of the equipment to floor

LED Music light RATstands Apollo Light 30

1 (bottom)

Equipment available does vary slightly according to equipment conditions and maintenance. Check with Technical Manager for any update.

1kW Strand Harmony F

Empty

660mm*

Empty

<u>Hirer will be provided with basic lighting only from available hung equipment, if technical preparation time is less than 2 hrs in the booking.</u>

All brought-in "Electrical and Stage Lighting Equipment" to be used in LCSD PA venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations (2009 Edition)". Please contact the venue management for any electrical safety concern. Website reference:

http://www.emsd.gov.hk/emsd/eng/welcome/em_safety.shtml

SOUND Sound System	Meyer M1D Meyer MINA Meyer ULRA-X42 Meyer MM-4XP Meyer 700-HP	(main central cluster) (main left & right) (delay loudspeaker for balcony) (front fill loudspeaker) (subwoofer loudspeaker)	8 12 3 6 2		
Main Control Console	DiGiCo Quantum 338, digital mixing console with 36 channels (Aux output x 10, Group output x 14, Matrix output x 12) in control room at rear of auditorium				
Microphone tie line	apron curtain line stage house 4 corner orchestra pit centre and rear audit catwalk (3 bridges) Multicore (16 chan orchestra pit, and rea	orium nels) inlets at stage left, stage r	9 7 24 8 8 6 ight, 4 sets		
Accessory	Klark Teknik DN-500	compressor/ limiter/ expender	2		
Electronics	Yamaha SPX-990	1			

V. 2024.04.11 Page 7 of 8

Microphone	(Pre-aligned, not loose equipment)	TC Electronics M3000 Studio Reverb Processor	1
AKG-C414 XLS			
AKG C-411 AKG C-409 AKG C-409 AKG C-409 AKG C-409 AKG C-409 AUdio Technica ATM-73a B&K 4007 Crown PCC-160 Crown PCC-160 Crown PZM-30D DPA 4099 Neumann KM-184 Neumann KM-184 Neumann KM-811 Neumann KMR-821 Sanken COS-11D-BK Sennheiser 421-II Shure Beta 57 Shure Beta 88 Shure Beta 87 Shure Beta 88 Shure Beta 88 Shure Beta 89	Microphone	AKG-C414 XLS	4
AKG C-418			
AKG C-419 AKG C-419 AUdio Technica ATM-33a Audio Technica ATM-73a B&K 4007 Crown PCC-160 Crown PCC-160 Crown PCC-180 Crown PZM-30D DPA 4099 Neumann KM-184 Neumann KM-185 Neumann KMR-81i Neumann KMR-81i Neumann KMR-81i Neumann KMR-82i Sanken COS-11D-BK Sennheiser 421-II Shure Beta 52A Shure Beta 57 Shure Beta 57 Shure Beta 57 Shure Beta 87 Shure Beta 91 Wireless Microphone Max. 8 units with a minimum booking of 2 sessions Stage Monitor Meyer UJ-1XP Meyer MJF-210 Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player Multi-media Equipment Computer Controlled surtitles projection system: Horizontal billingual surtitles projection system: Panasonic PT-RX110LB DLP Projector w/ ET-DLE350 I long zoom lens Panasonic PT-RX110LB DLP Projector w/ ET-DLE350 I long zoom lens Panasonic PT-RX110LB DLP Projector w/ ET-DLE350 I long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-DLE350 I long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-DLE350 I long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-DLE350 I long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-DT-SLE30 zoom I lens VIDEO FACILITIES Rolled Projection Screen 12' x 12' (W x H) Immediately DS of False Proscenium I communication			
AKG C-419 Audio Technica ATM-73a BaK 4007 Crown PCC-160 Crown PCC-160 Crown PCM-30D DPA 4099 Neumann KM-184 Neumann KM-185 Neumann KMR-811 Neumann KMR-811 Neumann KMR-821 Sanken COS-11D-BK Sennheiser 421-II Shure Beta 57 Shure Beta 57 Shure Beta 57 Shure Beta 57 Shure Beta 58 Shure Beta 88 Shure Beta 87 Shure Beta 89 Shure Beta 87 Shure Beta 80 Sennheiser SK 2000-Dw wireless microphone (clip) 8 Microphone Meyer UJ-1XP Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player Multi-media Equipment Horizontal bilingual surtitles projection system: Horizontal bilingual surtitles projection system: Horizontal bilingual surtitles projection system: Panasonic PT-RX110LB DLP Laser Projector W ET-DLE350 Long zoom lens Panasonic PT-RX110LB DLP Laser Projector W ET-DLE350 Long zoom lens Panasonic PT-DW17K2 DLP Projector W ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H)			
Audio Technica ATM-33a 4 Audio Technica ATM-73a 2 2 8&K 4007 1 1 1 1 1 1 1 1 1			
Audio Technica ATM-73a 2			
B&K 4007			
Crown PCC-160			
Crown PZM-30D 2			
DPA 4099 Neumann KM-184 Neumann KM-185 4 Neumann KM-185 4 Neumann KMR-81i 2 Neumann KMR-82i 5 Sanken COS-11D-BK 2 Sennheiser 421-II 4 Shure Beta 57A 4 Shure Beta 57A 4 Shure Beta 57A 4 Shure Beta 87 2 Shure Beta 91 1 Shure Beta 87 2			
Neumann KM-184 Neumann KM-185 A			
Neumann KMR-81 4			
Neumann KMR-81			
Neumann KMR-82i 5 Sanken COS-11D-BK 2 Sanken COS-11D-BK 2 Sennheiser 421-II 4 4 Shure Beta 574 4 Shure Beta 57 4 4 Shure Beta 57 4 4 5 Shure Beta 57 4 4 5 Shure Beta 57 4 4 5 Shure Beta 58 8 5 Shure Beta 58 8 Shure Beta 58 8 Shure Beta 87 2 5 Shure Beta 87 2 Shure Beta 87 3 Shure Beta 87 4 Shure Beta 87 4 Shure Beta 87 4 Shure Beta 87 5 Shure			
Sanken COS-11D-BK 2 2 Sennheiser 421-II 4 4 5 1 5 1 1 4 5 1 5 1 1 5 1 5 5 5			
Shure Beta 52A 1 1 1 1 1 1 1 1 1		Sanken COS-11D-BK	
Shure Beta 57 4 4 5 5 5 4 5 5 5 4 5 5		Sennheiser 421-II	4
Shure Beta 57A 4 5 5 5 4 5 5 5 4 5 5		Shure Beta 52A	1
Shure SM-58S Shure Beta 58 Shure Beta 58 Shure Beta 87 2 2 2 2 2 2 2 2 2		Shure Beta 57	4
Shure Beta 58 Shure Beta 87 2 2 2 2 2 2 2 2 2			4
Shure Beta 87 2 2 2 2 2 2 2 3 3 4 4 4 4 4 4 4 4			
Shure Beta 87A 2 1			
Shure Beta 91			
Wireless MicrophoneSennheiser SK 2000-Dw wireless microphone (clip) Sennheiser SKM 2000 BK-Dw (hand-held) Max. 8 units with a minimum booking of 2 sessions8Stage MonitorMeyer UPJ-1XP Meyer MJF-210 Meyer UMS-1P Meyer MJF-20810CDTascam-SS-CDR2002DVD PlayerJVC SR-HD2700E Blu-ray player2Multi-media 			
MicrophoneSennheiser SKM 2000 BK-Dw (hand-held) Max. 8 units with a minimum booking of 2 sessions8Stage MonitorMeyer UPJ-1XP Meyer MJF-210 Meyer UMS-1P Meyer UMS-1P Meyer MJF-20810CDTascam-SS-CDR2002DVD PlayerJVC SR-HD2700E Blu-ray player2Multi-media EquipmentComputer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens1VIDEO FACILITIES Rolled Projection Screen10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4)1COMMUNICATION1		Shure Beta 91	1
Stage Monitor Meyer UPJ-1XP Meyer MJF-210 Meyer UMS-1P Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player Multi-media Equipment Equipment VIDEO FACILITIES Rolled Projection Screen Max. 8 units with a minimum booking of 2 sessions Meyer UPJ-1XP Meyer MJF-210 2 2 2 2 2 3 4 4 5 7 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8 7 8		,	
Stage Monitor Meyer UPJ-1XP 10 Meyer MJF-210 2 Meyer UMS-1P 2 Meyer MJF-208 2 2	Microphone		G
Meyer MJF-210 Meyer UMS-1P Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player JVC SR-HD2700E Blu-ray player Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION		max. 6 and 6 with a minimum booking of 2 363316113	
Meyer MJF-210 Meyer UMS-1P Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player JVC SR-HD2700E Blu-ray player Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION	Stage Monitor	Meyer LIP.I-1XP	10
Meyer UMS-1P Meyer MJF-208 CD Tascam-SS-CDR200 DVD Player JVC SR-HD2700E Blu-ray player Equipment Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen To.50 x 6.50M (W x H) Immediately DS of False Proscenium 1 COMMUNICATION	Otago momen		
CD Tascam-SS-CDR200 2 DVD Player JVC SR-HD2700E Blu-ray player 2 Multi-media Equipment Computer Controlled surtitles projection system: 1 Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 2 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom 1 lens VIDEO FACILITIES Rolled Projection Screen (Bar 4) 12' x 12' (W x H) 1 mmediately DS of False Proscenium 1 COMMUNICATION			2
DVD Player JVC SR-HD2700E Blu-ray player Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION			
DVD Player JVC SR-HD2700E Blu-ray player Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION			_
Multi-media Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 2 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom 1 lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium 1 (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION	CD	Tascam-SS-CDR200	2
Equipment Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION	DVD Player	JVC SR-HD2700E Blu-ray player	2
Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 2 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom 1 lens VIDEO FACILITIES Rolled Projection Screen (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION			1
Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens VIDEO FACILITIES Rolled Projection Screen (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION		Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350	2
Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION		Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom	1
Rolled Projection Screen 10.50 x 6.50M (W x H) Immediately DS of False Proscenium (Bar 4) 12' x 12' (W x H) 1 COMMUNICATION	VIDEO FACII ITIES		
12' x 12' (W x H) 1 COMMUNICATION	Rolled Projection		1
		, ,	1
	COMMUNICATION		
SERVICE CONTROL DESCRIPTION OF SERVICE STATES		tuel namel at atoma right	
Stage manager control panel at stage right	Stage manager con	itroi panei at stage rignt	

V. 2024.04.11 Page 8 of 8

Dual channels intercom system with single/ dual channel(s) body-pack

Single channel wireless body-pack

Cue light system

Front-of-house paging/ Public address, Backstage paging/ Show relay system

Close Circuit TV

High Resolution camera and infra-red camera for stage house

system

Infra-red camera for auditorium

CCTV at stage manager's desk, side stage left and right

CCTV at G/F left and right stalls lobby entrance and 1/F balcony foyer

Production desk Set at the centre of the stall upon request

EMERGENCY FOH ANNOUNCEMENT SYSTEM

UPS maintained FOH emergency announcement system with hand-held wired microphone and digital playback.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment.

All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal.